




## High volume drainer 'D' pump

Pump end specification		
	Metric	US
Capacity	120 m <sup>3</sup> /h	528 gpm
Total Head	26 m	85 ft
Max. Solids Size	29 mm	1.14 in
Self Priming Lift	8.8 m	29 ft
Air Handling	4.25 l/s	8.8 cfm
Selprime® Absorbs	0.9 kW	1.2 hp
Power Required	6.5 kW	9 hp
Pump Speed Max.	2000	2000
Pump Speed Min.	955	955
Impeller Type	Drainer	Drainer
Impeller Blades	3	3
Impeller Diameter	192 mm	7.6 in
Inlet Port	DN 80 PN6	3 PN6
Outlet Port	DN 80 PN6	3 PN6
Length	81 cm	32 in
Width	43 cm	16.9 in
Height	58 cm	22.8 in
Weight	162 Kg	357 lb

**Priming method - Selprime®**

The unique original Selwood self priming system utilising a water tolerant diaphragm air pump. An environmentally friendly design that has none of the problems of oil vapour emissions and oil emulsification associated with other priming systems.

Pump end materials	
Pump Casing	Grey Iron BSEN 1561 Grade EN-GJL-250
Impeller	Cast Iron BSEN 1563 Grade EN-GJS-450-10
Wear Plates	Cast Iron BSEN 1563 Grade EN-GJS-600-3
Shaft	Steel BS En 10277 Grade C40+C
NRV Body	Grey Iron BSEN 156 Grade EN-GJL-250
Mechanical Seal	Ceramic / Sealide
Pump End Bearing	Ball
Drive End Bearing	Cylindrical Roller



**Please note:** The above curves cover the complete range and ability of the pump unit. Actual performance will be subject to the engine / motor indicated overleaf and medium pumped.

## High volume drainer 'D' pump builds

Our 'D Pumps' offer high efficiency centrifugal pumps for high-volume fluid transfer.

Handling flows of up to 90 m<sup>3</sup>/h, these highly efficient Selprime® pumps are easy to operate and maintain and have a robust construction.

Perfect for use with

- water – clean, with fine or larger solids
- screened sewage

### Reducing environmental impact

We are committed to reducing our environmental impact by producing the most efficient equipment we can.

All Selwood Eco5 pumps can run on hydrotreated vegetable oil (HVO) fuel as an alternative to diesel.



Standard builds	Isuzu 2 Wheel Site* Eco5		Isuzu Super Silent Eco5		Electric Static		Electric Static		Electric Static	
	Metric	US	Metric	US	Metric	US	Metric	US	Metric	US
Length	194 cm	76 in	176 cm	69 in	126 cm	50 in	126 cm	50 in	125 cm	49 in
Width	100 cm	39 in	114 cm	45 in	54 cm	21 in	54 cm	21 in	67 cm	26 in
Height	129 cm	51 in	157 cm	62 in	77 cm	31 in	77 cm	31 in	78 cm	31 in
Dry Weight	520 kg	1146 lbs	957 kg	2110 lb	259 kg	571 lb	265 kg	584 lb	350 kg	772 lb
Gross Weight	550 kg	1213 lbs	1025 kg	2260 lb	259 kg	571 lb	265 kg	584 lb	350 kg	772 lb
Sound Power	101 LWA	101 LWA	90 LWA	90 LWA	93 LWA	93 LWA			90 LWA	90 LWA
Sound Pressure @ 1m (3ft)	79 db(A)	79 db(A)	70 db(A)	70 db(A)	71 db(A)	71 db(A)	TBA	TBA	79 db(A)	79 db(A)
Sound Pressure @ 7m (23ft)	70 db(A)	70 db(A)	61 db(A)	61 db(A)	62 db(A)	62 db(A)			62 db(A)	62 db(A)
Engine / Motor	Isuzu 2CA1	Isuzu 2CA1	Isuzu 2CA1	Isuzu 2CA1	3.7 kW 230/1/50	5 HP	4 kW 380-415/3/50	5.3 HP	7.5 kW 400/3/50	10 HP
Emission / Electrical Rating	Stage V	Tier 4	Stage V	Tier 4	IE3	-	IE3	-	IE3	-
Engine / Motor Max Speed	2000 rpm	2000 rpm	2000 rpm	2000 rpm	1430 rpm	1430 rpm	1420 rpm	1420 rpm	2000 rpm	2000 rpm
Fuel Tank Capacity.**	36 lt	9.5 US gal	120 lt	31.7 US gal	-	-	-	-	-	-
BEP - Fuel Consumption	1.7 lt/hr	0.45 US gal/hr	1.7 lt/hr	0.45 US gal/hr	-	-	-	-	-	-


\*Open sets exclude fittings

\*\* Fuel tank capacity can be increased with the addition of an auxiliary fuel tank.

Installation drawings are available upon request.

### Optional extras

- Training
- Genuine parts kits
- Valves / Fittings
- Pump accessories
- Hose / pipework
- Auto stop/start control panels
- Pump telemetry
- Oil drain kit
- Bulk fuel kit
- Tanks & filtration
- Pipe stoppers
- Chalwyn valve & spark arrestor



**SELWOOD**  
www.selwood.co.uk

UK Rental  
03330 142000

UK Sales  
023 8025 0137

International Sales  
+44 23 8025 0137

Head Office Bournemouth Road, Chandler's Ford, Eastleigh, Hampshire, SO53 3ZL. T 023 8026 6311 E info@selwood.co.uk