


Hydraulic submersible pumps

Our 'HS Pumps' are designed for working at greater depths and include a choice of solids, drainer, high head or chopper pumps.

HS100 pumps are supplied in cast iron for greater durability. Depending upon the pumps primary type they are equally efficient for use with:

- Clean water
- Water with fine or large solids
- Water with rags and fibres
- Raw and screened sewage
- Sludge or slurry

Our customers include those in the following industries: construction and civil engineering, water and wastewater, ground stabilisation and piling, municipal, industrial, oil spill recovery and pollution control.



Pump specification	HS100D 100mm Drainer Pt No. 1745030008		HS100C 100mm Chopper Pt No. 1745030010		HS100H 100mm High Head Pt No. 1745030012		HS100SC 100mm Screw Pt No. 1745030094	
	Metric	US	Metric	US	Metric	US	Metric	US
Capacity	185 m³/h	815 USgpm	146 m³/h	643 USgpm	130 m³/h	572 USgpm	165 m³/h	726 USgpm
Total Head	23 m	75 ft	26 m	85 ft	69 m	226 ft	38 m	124 ft
Max. Solids Size	50 mm	2 in	50 mm	2 in	10 mm	0.3 in	50 mm	2 in
Length	350 mm	14 in	350 mm	14 in	350 mm	14 in	350 mm	14 in
Width	475 mm	19 in	475 mm	19 in	475 mm	19 in	475 mm	19 in
Height	740 mm	29 in	774 mm	30 in	740 mm	29 in	894 mm	35 in
Weight	54 kg	119 lb	54 kg	119 lb	54kg	119 lb	54kg	119 lb
For use with the following Powerpack	HSP20, HSP20Eco, HSP20Eco5		HSP20, HSP20Eco, HSP20Eco5		HSP35, HSP35Eco		HSP35, HSP35Eco	