HSP110

Hydraulic submersible power pack

Our 'HS Pumps' are designed for working at greater depths and include a choice of solids, drainer, high head or chopper pumps.

Options include multiple hydraulic circuits, up to 100m hydraulic hoses, 24hr running and emission compliant engines. These electric start diesel driven hydraulic power packs fully protected by an automatic shutdown system.

The hydraulic system can run on synthetic biodegradable or vegetable oil which significantly reduces harmful environmental pollution. The hydraulics incorporate a large return filter ensuring that any contaminants are captured and the fuel tank has flushing panels and a drain facility.

Equally efficient for use with

- Clean water
- Water with fine or large solids
- Water with rags and fibres
- Raw and screened sewage
- Sludge or slurry

Standard build	Deutz Super Silent - RENTAL ONLY	
	Metric	US
Length Width Height	260 cm 142 cm 221 cm	102 in 56 in 87 in
Dry Weight Gross Weight	2750 kg 3017 kg	6063 lbs 6651 lbs
Sound Power Sound Pressure @ 1m (3 ft) Sound Pressure @ 7m (23 ft)	Awaiting test	
Engine	Deutz TCD3.6	
Emission Rating	Stage IIIB	-
Engine Max Speed	2000 rpm	
Fuel Tank Capacity.	320 lt	84 US gal
BEP - Fuel Consumption	lt/hr depends upon pump	US gal/hr depends upon pump

Optional Extras

Auto stop/start control

■ Hose / pipework

- Training
- Genuine parts kits
- Valves / Fittings
- Pump accessories
- Pump telemetryOil drain kit

panels

- Tanks & filtrationPipe stoppers
- Chalwyn valve & spark
- arrestor
- HS pumps see right



Wet Ends available as Optional Extras



HS200D - Drainer



Seldredge (SC / C)

Please see the specific Data Sheet for each of these pumps, which will show technical information as well as the performance curve.

SEL	WOOD	
www.selwood.co.uk		

 Head Office
 Bournemouth Road, Chandler's Ford, Eastleigh, Hampshire, SO53 3ZL
 UK.

 T +44(0)23 8026 6311
 E info@selwood.co.uk
 E